# Progress on the Conceptual Design of the Laser-hybrid Accelerator for Radiobiological Applications (LhARA)







**THPM083** 


W. Shields <sup>1</sup> on behalf of the LhARA Collaboration <sup>1</sup> John Adams Institute, Royal Holloway, University of London

#### Abstract

LhARA, the Laser-hybrid Accelerator for Radiobiological Applications, is a proposed novel facility capable of delivering high intensity beams of protons and ions that will enable radiobiological research to be carried out in completely new regimes. A two-stage facility, the first stage utilizes laser-target acceleration to produce proton bunches of energies up to 15 MeV. A series of Gabor plasma lenses will efficiently capture the beam which will be delivered to an in-vitro end station. The second stage will accelerate protons in a fixed-field alternatinggradient ring up to 127 MeV, and ions up to 33.4 MeV/nucleon. The beams will subsequently be deliverable to either an in-vivo end station or a second in-vitro end station. The technologies demonstrated in LhARA have the potential to underpin the future of hadron therapy accelerators and will be capable of delivering a wide variety of time structures and spatial configurations at instantaneous dose rates up to and significantly beyond the ultra-high dose rate FLASH regime. We present here recent progress and the current status of the LhARA accelerator as we work towards a full conceptual design.


#### LhARA Baseline Design

- LhARA is a proposed state-of-the-art accelerator for radiobiological research that serves the Ion Therapy Research Facility (ITRF).
  - We aim to develop & demonstrate novel technologies for generating and delivering proton & ion beams at FLASH dose rates.
  - A systematic radiobiology program is in development, laying the foundations for future generations of radiotherapy.
- LhARA is conceived to be developed in two stages [1,2]:
  - Stage 1 will generate high flux beams from a laser-target interaction via the Target Normal Sheath Acceleration (TNSA) mechanism.
  - Gabor electron plasma lenses will capture & focus the beam.
  - Stage 2 accelerates the beam in an FFA ring, with an extraction line transporting the beams to two further end stations.




- Work towards a full conceptual design is underway. Here, we show progress on understanding of the generated beam and subsequent tracking performance.
  - A broader update on the status of LhARA can be found in [3].

## Simulated TNSA Beam & Transport Performance




- LhARA's baseline design modelled beams simulated by the laser-target interaction PIC code Smilei [5]
- Computational resources limited the beam to 2D, with the third dimension generated by extrapolation [6].
- New full 3D simulations with the PIC code OSIRIS [7] modelled the SCAPA facility
- Similarities shared with the proposed LhARA setup.
- Normal laser angle of incidence.
- Beam down-sampled to the nominal 15 MeV +/- 2%.



Beam	Emittance (m)	Beta (m)	Alpha
Pre-CDR	$3.26 \times 10^{-7}$	4.89	-50.22
Smilei	$1.43 \times 10^{-8}$	141.34	-1418.43
SCAPA	$7.98 \times 10^{-8}$	21.62	-222.23


- A slight horizonal asymmetry is observed in the beam phase space, however downstream transport performance is not adversely affected.
- The beam remains highly divergent as a result of space charge forces
  - The temporal and spectral profiles remain approximately uniform over the regions of interest.

- BDSIM [3] and GPT [4] are used in start-toend Monte Carlo simulations.
- Space-charge modelling revealed further emittance growths.
- Model optimized for:
  - A parallel beam after Gabor lenses 2 & 5
- A beam waist at the energy collimator




- Although successful, solutions for smaller spot sizes remain challenging.
- End station spot-size flexibility is impacted
- Stage 2 FFA injection conditions (Twiss  $\beta = 50$ m) are crucial to meet.

## Experimental 7 Gabor Lens Configuration for Flexibility



- A promising new configuration is being investigated that includes two further Gabor lenses.
  - Modelled 2.5m downstream of Gabor lens 5, in the same configuration as Gabor lenses 4 & 5, between which an additional 20 cm drift length is included.
  - Only one collimator required for both stage 1 and stage 2 operation. The total beam line length increase is 5.314 m.
- The SCAPA beam is tracked in MADX, BDSIM, and GPT models (excluding space charge effects) for validation, with good agreement observed.
  - Transport performance is once again impeded when space charge effects are considered, with further emittance growths observed.



### Summary

An improved understanding of LhARA's laser-target generated beam has highlighted potential issues with the flexibility & stage 2 operation of the baseline design. Whilst optimization of the nominal optics configuration has been achieved, the requirement for smaller spot-sizes has prompted an investigation into a promising new configuration with seven Gabor lenses. Optimization of this design has yielded improved flexibility performance. Research remains ongoing to assess the feasibility of this new configuration.

# References

- [1]: The Laser-hybrid Accelerator for Radiobiological Applications, Imperial College, UK, Rep. CCAP-TN-01, 2020.
- [2]: G. Aymar et al., Frontiers in Physics, vol. 8, 2020.
- [3]: C. Whyte, presented at the 14th Int. Particle Accelerator Conf. (IPAC'23), Venice, Italy, May 2023, paper THPM066, this conference.
- [3]: L.J. Nevay et al., Computer Physics Communications, vol. 252, pp. 107200, 2020.
- [4]: General Particle Tracer, http://www.pulsar.nl/gpt/index.html [5]: J. Derouillat et al., Computer Physics Communications, vol. 222, pp. 351-373, 2018.
- [6]: H.T. Lau et al., Proc. 12th Int. Particle Accelerator Conf. (IPAC'21), Campinas, SP, Brazil, 2021, pp. 2939-2942
- [7]: R. A. Fonseca *et al.*, *Lect. Notes Comput. Sci.*, vol. 2331, pp. 342, 2002

# Contacts

- John Adams Institute for Accelerator Science, Royal Holloway, University of London
- Email: william.shields@rhul.ac.uk
- Website: <u>www.lhara.org</u>